

**MULTIGRAB / 7-SERIES**


GLOBRAM MULTIGRAB, 7-SERIES		RM 707	RM 711	RM 718	RM 725	RM 732	RM 739
Excavator weight min	ton	3	5	12	17	22	26
Excavator weight max	ton	10	16	22	30	40	50
Excavator weight optimum min	ton	4	6	14	19	24	28
Excavator weight optimum max	ton	10	16	22	30	40	50
Max. working pressure	bar	300	300	300	320	350	350
Max. oil delivery	l/min	30	50	70	80	130	160
Hydraulic connection cylinder	inch	1 / 2"	1 / 2"	3 / 4"	3 / 4"	3 / 4"	3 / 4"
Max. rotation pressure	bar	100	100	100	110	110	110
Max. rotation oil flow	l/min	10	10	20	20	30	30
Hydraulic connections for rotation	inch	3 / 8"	3 / 8"	1 / 2"	1 / 2"	1 / 2"	1 / 2"
Max. force at blade/teeth	kg	3000	4000	6000	7000	10000	12000
Cradle plate compatibility		RM 88	RM 88	RM 120 - 130	RM 120 - 130	RM 140 - 150	RM 140 - 150
Cradle plate dimensions	mm	430 x 360 12 x Ø 22	430 x 360 12 x Ø 22	640 x 480 12 x Ø 22	640 x 480 12 x Ø 22	730 x 550 12 x Ø 27	730 x 550 12 x Ø 27

SORTING JAWS		RM 707S	RM 711S	RM 718S	RM 725S	RM 732S	RM 739S
Attachment operating weight (incl. bracket)	kg	380	570	1140	1610	2180	2650
Max. opening	mm	1500	1700	2200	2500	2700	3000
Load capacity	mm	170	280	550	800	1200	1500
Jaw width	mm	600	700	900	1000	1100	1200

DEMOLITION JAWS		RM 707D	RM 711D	RM 718D	RM 725D	RM 732D	RM 739D
Attachment operating weight (incl. bracket)	kg	400	600	1200	1700	2300	2800
Max. opening	mm	1500	1700	2200	2500	2700	3000
Load capacity	mm	170	280	550	800	1200	1500
Jaw width	mm	600	700	900	1000	1100	1200

MATERIAL HANDLING JAWS		RM 707H	RM 711H	RM 718H	RM 725H	RM 732H	RM 739H
Attachment operating weight (incl. bracket)	kg	425	640	1280	1800	2450	2990
Max. opening	mm	930	1085	1360	1550	1710	1840
Load capacity	mm	350	550	1090	1625	2170	2710
Jaw width	mm	570	660	830	950	1050	1130

LOADING JAWS		RM 707L	RM 711L	RM 718L	RM 725L	RM 732L	RM 739L
Attachment operating weight (incl. bracket)	kg	415	630	1250	1780	2400	2930
Max. opening	mm	1500	1700	2200	2500	2700	3000
Load capacity	mm	190	320	620	900	1350	1700
Jaw width	mm	600	700	900	1000	1100	1200

TIMBER JAWS		RM 707T	RM 711T	RM 718T	RM 725T	RM 732T	RM 739T
Attachment operating weight (incl. bracket)	kg	415	630	1250	1780	2400	2930
Max. opening	mm	930	1090	1360	1550	1710	1840
Jaw width	mm	570	660	830	950	1050	1130