

STEEL SHEAR / 9-SERIES


GLOBRAM STEEL SHEARS, 9-SERIES		RM 9102	RM 9203	RM 9254	RM 9305	RM 9356	RM 9459
Min. Excavator weight as fixed 2nd member	ton	8	18	23	27	33	42
Min. Excavator weight as rotating 2nd member	ton	10	20	25	30	35	45
Min. Excavator weight as rotating 3rd member	ton	20	30	40	50	60	90
Attachment operating weight as fixed 2nd member	ton	2000	3250	4500	5600	7200	9700
Attachment operating weight as rotating 2nd member	ton	2400	3600	5000	6300	7800	11000
Attachment operating weight as rotating 3rd member	ton	2400	3650	4800	6100	7800	10400
Max. working pressure	bar	400	400	400	400	400	400
Oil delivery	l/min	100 - 200	200 - 300	220 - 360	240 - 400	300 - 550	360 - 700
Oil flow max. rotation	l/min	20	30	40	50	50	60
Pressure max. rotation	bar	110	110	110	130	130	130
Max. clamping force at tip	ton	120	140	190	210	240	275
Clamping force class	ton	600	800	1000	1300	1500	2500
Length	mm	2724	3400	3800	4040	4238	4840
Jaw width	mm	450	560	640	680	730	815
Jaw opening	mm	550	660	740	850	950	1100
Max. jaw depth	mm	570	680	760	860	970	1120
Closure time	sec	2,4 - 4,6	2,8 - 4	3,2 - 5	3,6 - 5,8	3,6 - 6,4	3,8 - 7,2
Opening time	sec	2,2 - 4,2	2,6 - 3,8	2,8 - 4,8	3,4 - 5,6	3,2 - 5,6	3,6 - 7
Cradle plate compatibility		RM 140 - 150	RM 180 - 195	RM 180 - 195	RM 180 - 195	RM 215 - 250	RM 215 - 250
Cradle plate dimensions	mm	730 x 550 12 x Ø 27	740 x 740 12 x Ø 39	740 x 740 12 x Ø 39	740 x 740 12 x Ø 39	1090 x 1090 20 x Ø 39	1090 x 1090 20 x Ø 39