

PULVERIZER FIXED / 4-SERIES


GLOBRAM PULVERIZERS fixed, 4-SERIES		RM 412X	RM 416X	RM 426X	RM 436X	RM 443X	RM 450X
Excavator weight min	tons	6	10	16	20	28	33
Excavator weight max	tons	18	21	30	45	55	65
Excavator weight optimum min	tons	7	12	18	24	30	36
Excavator weight optimum max	tons	18	21	30	45	55	65
Attachment operating weight (incl. bracket)	kg	750	1300	1800	2800	3450	4400
Max. opening	mm	650	810	900	1000	1190	1290
Height	mm	1700	1900	2100	2440	2590	2850
Width	mm	980	1190	1470	1540	1630	1800
Jaw width	mm	345	400	450	520	560	610
Oil delivery min	l/min	80	120	140	150	180	180
Oil delivery max	l/min	200	200	220	250	260	300
Max. working pressure	bar	350	400	400	400	400	400
Max. clamping force at tip	ton	50	65	80	105	120	135
Max. clamping force at shears	ton	160	210	265	355	380	410
Shear length	mm	100	180	240	240	240	360
Max. cutting diameter	mm	40	40	45	50	50	50
Min. closure time	sec	2	2	3	2	2,5	2,5
Min. opening time	sec	1	1	1,5	2	2,5	2,5
Hydraulic connections open/close	inch	3 / 4"	3 / 4"	3 / 4"	1"	1"	1"
Cradle plate compatibility		RM 90	RM 120 - 130	RM 140 - 150	RM 160	RM 180 - 195	RM 180 - 195
Cradle plate dimensions	mm	540 x 420 12 x Ø 22	640 x 480 12 x Ø 22	730 x 550 12 x Ø 27	750 x 750 12 x Ø 30	740 x 740 12 x Ø 39	740 x 740 12 x Ø 39