

COMPACTOR WITH ROTATION / 6R-SERIES


GLOBRAM COMPACTORS rotation, 6R-SERIES		RM 606R	RM 609R	RM 612R	RM 618R	RM 630R
Excavator weight min	tons	3,5	6,5	7	15	16
Excavator weight max	tons	13	16	16	25	45
Excavator weight optimum min	tons	3,5	6,5	7	15	16
Excavator weight optimum max	tons	13	16	16	25	45
Attachment operating weight (incl. bracket)	kg	425	630	670	1185	1520
Height	mm	88	93	93	108,6	110,6
Baseplate	mm	30x76	46x84	64x87	71x120	90x122
Centrifugal force	kN	3000 , 29.5	4000 , 39	4000 , 39	10000 , 98	17000 , 167
Compacting force	N/cm ²	1.7 , 16.7	1.1 , 10.8	1.1 , 10.8	1.8 , 17.7	2.2 , 21.6
Oil flow to motor	l/min	45 - 70	75	75	120	190 - 265
Max. working pressure	bar	200	200	200	200	200
Oil delivery to rotation	l/min	10	10	10	10	10
Max. working pressure rotation	bar	90	90	90	90	90
Cradle plate compatibility		RM 88	RM 88	RM 88	RM 110 - 115	RM 120 - 130
Cradle plate dimensions	mm	430 x 360 12 x Ø 22	430 x 360 12 x Ø 22	430 x 360 12 x Ø 22	750 x 750 12 x Ø 30	640 x 480 12 x Ø 22